

## More engaging, productive and collaborative meetings

Designed for easy video conferencing and content sharing, Samsung QBB and QMB series commercial displays help facilitate presentations, brainstorming and decision-making. Transform meeting spaces into smart, connected spaces where your hybrid workforce can collaborate more productively.

4K

### Impactful and immersive 4K UHD

Smooth, ultra-high resolution video and picture quality offer a crisp, clear picture that's four times the detail of Full HD. It brings extra clarity to displays, especially when viewed up close.



### True-to-life colors for engaging visuals

Dynamic Crystal Color can reproduce a billion shades of color, enhancing presentations with exceptionally vivid, lifelike hues.



### Never miss a detail

Our powerful Quantum Processor 4K upscales every piece of content into crisp 4K, for consistently exceptional picture quality. High Dynamic Range enhances color, clarity and contrast.



### Anti-glare for clarity from everywhere

The anti-glare panel in the QMB series and the 178 degree viewing angles ensure optimal readability in any viewing condition.



### Plug and play video conferencing for hybrid working

QBB/QMB series displays feature a built-in solution that makes video conferencing easier than ever. They support the most popular web conferencing apps, and enable simple video calls with your third-party USB-type webcam.<sup>1</sup>



### Cisco Webex® certified

QBB/QMB series displays have undergone the most stringent of all testing by the Webex Device Business Unit and are fully certified. Combined with Cisco Webex®, QBB/QMB series displays provide the ultimate conferencing solutions.



### Share your screen from any device

SmartView+ enables wireless screen sharing without cables, for a hassle-free way for guests and visitors to share their screen and collaborate real-time.<sup>2</sup>



### Simplified room management

Custom Home feature allows admins to lock settings, preventing users from changing settings between meetings.



### Easy installation and management

Tizen Zero Config simplifies installation of multiple displays in different locations by pushing initial set-up settings to all displays at the touch of a button.<sup>3</sup> Then manage them all from a single location.



### Reliable operation, 3-year warranty

The QBB series is engineered for dependable 16/7 operation, while the QMB series offers 24/7 operation. The IP5x certification ensures complete dust protection, and a 3-year limited warranty provides peace of mind.




# QBB / QMB Series Displays

Specifications			QB43B	QM43B	QB50B	QM50B	QB55B	QM55B	QB65B	QM65B	QB75B	QM75B
Display Panel	Model Name		QB43B	QM43B	QB50B	QM50B	QB55B	QM55B	QB65B	QM65B	QB75B	QM75B
	Diagonal Size (Class/Measured)		43" / 42.5"		50" / 49.5"		55" / 54.6"		65" / 64.5"		75" / 74.5"	
	Resolution		3840 x 2160 (16:9)		3840 x 2160 (16:9)		3840 x 2160 (16:9)		3840 x 2160 (16:9)		3840 x 2160 (16:9)	
	Brightness (Typ.)		350 nit		350 nit		350 nit		350 nit		350 nit	
	Orientation		Landscape / Portrait		Landscape / Portrait		Landscape / Portrait		Landscape / Portrait		Landscape / Portrait	
	Antiglare		No		No		No		No		No	
Connectivity / Sound	Input		HDMI 2.0 (3)   DP1.2 (1), HDMI 2.0 (3)		HDMI 2.0 (3)   DP1.2 (1), HDMI 2.0 (3)		HDMI 2.0 (3)   DP1.2 (1), HDMI 2.0 (3)		HDMI 2.0 (3)   DP1.2 (1), HDMI 2.0 (3)		HDMI 2.0 (3)   DP1.2 (1), HDMI 2.0 (3)	
	Output		HDCP2.2   USB 2.0 x 2		HDCP2.2   USB 2.0 x 2		HDCP2.2   USB 2.0 x 2		HDCP2.2   USB 2.0 x 2		HDCP2.2   USB 2.0 x 2	
	Wi-Fi / Bluetooth		Wi-Fi (2.4/5.0GHz dual), Bluetooth RS232C (in/out), RJ45		Wi-Fi (2.4/5.0GHz dual), Bluetooth RS232C (in/out), RJ45		Wi-Fi (2.4/5.0GHz dual), Bluetooth RS232C (in/out), RJ45		Wi-Fi (2.4/5.0GHz dual), Bluetooth RS232C (in/out), RJ45		Wi-Fi (2.4/5.0GHz dual), Bluetooth RS232C (in/out), RJ45	
	External Control		10W, 2ch		10W, 2ch		10W, 2ch		10W, 2ch		10W, 2ch	
	Speaker		Stereo Mini Jack		Stereo Mini Jack		Stereo Mini Jack		Stereo Mini Jack		Stereo Mini Jack	
	Mechanical Specs	Dimensions		Set Package 38.09" x 21.96" x 1.9" 43.11" x 26.61" x 5.94"		Set Package 44.15" x 25.35" x 1.82" 49.96" x 30.87" x 5.98"		Set Package 48.63" x 27.87" x 1.82" 55.2" x 33.78" x 6.42"		Set Package 57.24" x 32.72" x 1.82" 63.43" x 38.31" x 7.28"		Set Package 66.19" x 37.8" x 1.96" 73.66" x 44.37" x 8.78"
Weight		Set Package 22.05 lbs. 29.32 lbs. 200 x 200		Set Package 29.54 lbs. 38 lbs. 200 x 200		Set Package 39.9 lbs. 52.03 lbs. 200 x 200		Set Package 54.9 lbs. 73.41 lbs. 400 x 400		Set Package 84.44 lbs. 108.03 lbs. 400 x 400		
VESA Mount		200 x 200		200 x 200		200 x 200		200 x 200		200 x 200		
Bezel Width		9.2mm (U/L/R), 11.2mm (B)		9.2mm (U/L/R), 11.2mm (B)		9.2mm (U/L/R), 11.2mm (B)		9.2mm (U/L/R), 11.2mm (B)		11.5mm (U/L/R), 12.5mm (B)		
Features	Internal Player		Cortex A72 1.7GHz Quad-Core CPU 8GB		Cortex A72 1.7GHz Quad-Core CPU 8GB		Cortex A72 1.7GHz Quad-Core CPU 8GB		Cortex A72 1.7GHz Quad-Core CPU 8GB		Cortex A72 1.7GHz Quad-Core CPU 8GB	
	Storage (FDM)		16 GB		16 GB		16 GB		16 GB		16 GB	
	Hardware		Center IR, Temperature Sensor, Auto Level		Center IR, Temperature Sensor, Auto Level		Center IR, Temperature Sensor, Auto Level		Center IR, Temperature Sensor, Auto Level		Center IR, Temperature Sensor, Auto Level	
	Software		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC, mobile), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, Video Conference Solution		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC, mobile), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, Video Conference Solution		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC, mobile), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, Video Conference Solution		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC, mobile), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, Video Conference Solution		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC, mobile), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, Video Conference Solution	
Certification	Safety EMC		60950-1 / 62368-1 Class B		60950-1 / 62368-1 Class B		60950-1 / 62368-1 Class B		60950-1 / 62368-1 Class B		60950-1 / 62368-1 Class B	
	Environment		N/A		ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT	
	IP Rating		IP5x		IP5x		IP5x		IP5x		IP5x	
Power	Security		802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP		802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP		802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP		802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP		802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	
	Power Supply		AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz	
	Power Consumption		Max (W/h) 110 Typical (W/h) 79 Sleep Mode < 0.5W		143   171 91 < 0.5W		143   108 96 < 0.5W		182   127 124 < 0.5W		231   161 174 < 0.5W	
Operation Condition	Temperature		32°F-104°F		32°F-104°F		32°F-104°F		32°F-104°F		32°F-104°F	
	Relative Humidity		10-80%		10-80%		10-80%		10-80%		10-80%	
Accessories	Included		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries STN-14355G		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries STN-14355G		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries STN-14355G		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries No		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries No	
	Optional		Stand Mount Specialty WMN4070SG (Landscape Only), WMN750ME CML400XR		Stand Mount Specialty WMN4070SG (Landscape Only), WMN750ME CML400XR		Stand Mount Specialty WMN4070SG (Landscape Only), WMN750ME CML400XR		Stand Mount Specialty WMN4277SF (Landscape Only), WMN750ME CML450T		Stand Mount Specialty WMN4277SF (Landscape Only), WMN6575SF CML450T	

## Connectivity

1. USB 2 (1.0A)
2. USB 1 (0.5A)
3. Speaker Jack
4. HDMI (ARC)
5. HDMI
6. DP
7. RJ45
8. RS232C
9. RS232C
10. IR

QBB Series




Front



Back



QMB Series



Front



Back



Learn More [samsung.com/display](https://samsung.com/display) [samsung.com/business](https://samsung.com/business) [insights.samsung.com](https://insights.samsung.com)

Product Support 1-866-SAM4BIZ Follow Us [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

**SAMSUNG**

©2022 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All other brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screen images simulated. Non-metric weights and measurements are approximate. Specifications and designs are subject to change without notice. See [samsung.com](https://samsung.com) for detailed information. Printed in USA. DIGSIG-CORP-QBBQMB-DSHT-MAR22

\*Video Call Application will be available through a firmware update launching in Q2 2022. Webcam must be purchased separately. Supported cameras: Logitech C930e, C922, C922x, C925E, C920s, C920, C920-C, C930C, Stream Camera. †Windows, Android, iOS are supported. Mobile OS will be available via firmware update Q2 2022. ‡Tizen Zero Config will be available via firmware update Q2 2022.